

PETROL ENGINE DRIVEN HYDRAULIC POWER UNITS

ENGINE

ALL ENGINES COME WITH RECOIL START AS STANDARD. ELECTRIC START CAN BE SPECIFIED ON REQUEST. YOUR BATTERY MOUNTING REQUIREMENTS CAN BE DISCUSSED WITH OUR SALES TEAM.

HANDLE ASSEMBLY

FOLDING HANDLE FOR COMPACT STORAGE

GEAR PUMP

PUMP MOUNTED RELIEF VALVE. REDUCING THE NEED FOR COMPLEX PIPEWORK

HOSE

TOP QUALITY GATES FLEXIBLE HOSE USED THROUGHOUT

SUCTION STRAINER

125 MICRON SUCTION STRAINER FITTED AS STANDARD TO ASSIST IN KEEPING THE HYDRAULIC SYSTEM CLEAN. REDUCING WEAR AND MAINTENANCE COSTS.

RETURN FILTER AND MANIFOLD

RETURN FILTER FITTED WITH 10 MICRON FIBREGLASS ELEMENT AND FILTER GAUGE TO INDICATE WHEN REPLACEMENT IS DUE. MOUNTED DIRECTLY ONTO THE ACCESS MANIFOLD FOR EASE OF MAINTENANCE. MANIFOLD ALLOWS ACCESS TO THE INTERIOR OF THE TANK.

PRESSURE & TANK CIRCUIT

PRODUCT REFERENCE	ENGINE	FUEL TYPE	HORSE POWER	FLOW RATE	RESERVOIR SIZE	NETT. PRICE	
						£ STERLING	€ EUROS
ZZ003802	Honda GX160FQ	Petrol	5.5HP	10.5 L/min	50 Litres		
ZZ003801	Honda GX270FQ	Petrol	9HP	19.5 L/min	50 Litres		
ZZ003799	Honda GX390FQ	Petrol	13HP	25.5 L/min	50 Litres		
ZZ010354	Honda GX390FQ	Petrol	13HP	24 L/min	100 Litres		
ZZ003804	Loncin G160F-P	Petrol	5.5HP	10.5 L/min	50 Litres		
ZZ003803	Loncin G270F-P	Petrol	9HP	19.5 L/min	50 Litres		
ZZ003800	Loncin G390F-P	Petrol	13HP	25.5 L/min	50 Litres		