


FFS16/80T

Portable Hose Crimping Machine Max 1" 2-SN (DN25, -16)

The FFS16/80T is ideal for on-site hose repairs as it will help to repair hoses with uneasy access. The magnetic head of the FFS16/80T also allows you to position the head at an ideal height or safely position the head onto the boom of a machine where a hose needs to be repaired.













PRODUCT FEATURES

- SPLITTED HEAD AND PUMP CONCEPT
 - HEAD WITH MAGNET
- IDEAL FOR ON SITE HOSE REPAIRS

TECHNICAL SPECIFICATION

	Capacity: For hydraulic hose crimping and intermittent use	2-SN: 1" (DN25; -16) 4-SP: 1/2" (DN13; -10) Limit for assembly with 2 x 90° elbows: max 1/2" (DN13)
	Hand Pump	Double Stage 25cm3 + 5cm3, Max 320 Bar
	Radial Crimp force	80 tons
	Die opening	Ø Die. + 20mm
	Opening without dies	56 mm
	Head Dimensions	Width: 240mm Depth: 130mm Height: 240mm
	Pump Dimensions	Width: 360mm Depth: 130mm Height: 360mm
	Net weight (with oil, without dies)	20 Kg for one magnetic head (NKS16.1) 9 Kg for hand pump support with drawer (NKS16-HP1)
	Packing details (for transport purposes)	Wooden crate conform to ISPM15 Crate size: 26x41x48cms Gross weight (with 6 sets of dies): 35 Kgs

PRICE FOR MACHINE

ECT DI	ES EDON				
SELECT DIES FROM TABLE BELOW					
DIE SIZE Ø	HOSE SIZE	NETT.	PRICE		
		£ STERLING	€ EUROS		
10	*BY MAN				
12	*BY MAN				
15	*BY MAN				
18	**1/4"				
21	**3/8"				
24	**1/2"				
27	**5/8"				
30	**3/4"				
30	3/4"				
	10 12 15 18 21 24 27 30	10 *BY MAN 12 *BY MAN 15 *BY MAN 18 **1/4" 21 **3/8" 24 **1/2" 27 **5/8" 30 **3/4"	## NOSE SIZE NETT. ## E STERLING 10 "BY MAN 12 "BY MAN 15 "BY MAN 18 "*1/4" 21 "*3/8" 24 "*1/2" 27 "*5/8" 30 "*3/4"		

**The hose sizes stating hose size in table above are for use with Flowfits Vincke Hydraulic Hose!

*BY MAN = By Manufacturer, Hose size determined by hose manufacturers crimping data- <u>Please check with YOUR hose supplier!</u>