

FFSK50 2"

Skiving machine for rubber hoses up to 2" 6- Spiral

Compact Electric Hose skiving machine with clear plexiglass guard and safety features.

The machine is equipped with a switch to change the direction of the rotation and a foot switch. External skiving is done with pre-adjustable tools ESK and Internal Skiving with pre-adjustable tools ISK. Machines with Simultaneous internal and external skiving are also available (NSK50-SIM)

Skiving up to 2" Hose



EXTERNAL AND INTERNAL SKIVING

- MACHINE CONFORM TO CE SAFETY RULES
- HIGH QUALITY SKIVING THANKS TO SPECIAL KNIFE DESIGN
- SUPER CLEAR VISION THANKS TO ALL-PLEXY PROTECTION BOX

TECHNICAL SPECIFICATION

Hose capacity:	2SN: 2" (DN50) 4-SP: 2" (DN50) 6-SP: 2" (DN50)
Motor:	0,55KW-400V 50Hz 3-PH
Max hose OD:	Ø 95mm
Suppress Line Cutting Disc Size:	Ø 350mm (Slotted edge, HSS steel disc)
Rotation speed:	370 rpm Option: Speed Adjuster 0-400 rpm Standard Control: Foot Switch + Rotation direction switch
Dimensions:	Width: 240 x Depth 760 x Height 330mm
Net weight:	45 Kg
Packing:	Pallet 55x70x75cms, 55 Kgs
Skiving Tools / Available Options	External Skiving Tools ESK (Standard Pack includes 2 x ESK): ESK6-25 for hose 1/4" to 3/4" ESK32-50 for hose 1 1.4" to 2" Internal Skivers available (Optional): ISK Ø16,19,25,32,38,50 Other Options: Individual External Skiving Heads (1 per hose size) Support table with bin Hose clamping system for increased operator safety Simultaneous internal + external skiving