

SAFETY DATA SHEET

VARGEAR RANGE (ISO68 TO ISO460)

Page: 1

Compilation date: 13-05-2015

Revision date: 15-03-2018

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: * VARGEAR RANGE (ISO68 TO ISO460)

REACH registered number(s): NOT APPLICABLE

Product code: * GE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

1.3. Details of the supplier of the safety data sheet

Company name: Varol Lubricants

Shelah Rd

Halesowen

West Midlands

B63 3PN

United Kingdom

Tel: +44(0) 121 585 6006

Fax: +44(0) 121 585 5405

Email: datasheets@varol.co.uk

1.4. Emergency telephone number

Emergency tel: +44(0) 121 550 3406

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412

Most important adverse effects: Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H412: Harmful to aquatic life with long lasting effects.

Precautionary statements: P273: Avoid release to the environment.

P501: Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET
VARGEAR RANGE (ISO68 TO ISO460)

Section 3: Composition/information on ingredients

3.2. Mixtures

*** Hazardous ingredients:**

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC.

EINECS	CAS	PBT / WEL	CLP Classification	Percent
649-466-00 -2	64742-53-6	-	Asp. Tox. 1: H304	30-50%

AMINES, COCO ALKYL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
262-977-1	61788-46-3	-	Acute Tox. 4: H302; Asp. Tox. 1: H304; STOT SE 3: H335; STOT RE 2: H373; Skin Corr. 1B: H314; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	<0.25%

Non-classified ingredients:

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY PARAFFINIC

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-090-8	64741-88-4	-	-	50-70%

Contains: * Highly refined mineral oil - DMSO extract <3% (w/w) according to IP346

The highly refined base oil may be described by one or more of the following generic CAS identifiers: 64742-54-7, 64742-65-0, 64742-52-5, 64742-53-6, 64742-62-7, 64742-57-0, 64742-01-4, 64741-88-4, 64741-96-4, 64741-97-5, 64742-55-8, 64742-56-9, 64741-89-5, 64742-47-8, 8042-47-5.

The base oils may be used interchangeably to provide a product which is equivalent from both a regulatory and technical perspective.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

[cont...]

SAFETY DATA SHEET

VARGEAR RANGE (ISO68 TO ISO460)

Page: 3

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: * Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: * In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: * Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): * PC24: Lubricants, greases, release products.

[cont...]

SAFETY DATA SHEET

VARGEAR RANGE (ISO68 TO ISO460)

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: If user generates dust, fumes, gas vapor or mist use process enclosures, Local Exhaust Ventilation (LEV) or other engineering controls to keep worker exposure to airborne contaminants below any statutory or recommended limits.

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (oil-resistant).

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: The floor of the storage room must be impermeable to prevent the escape of liquids. Ensure all engineering measures mentioned in section 7 of SDS are in place. Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Oil

Colour: Amber

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Oily

Kinematic viscosity: See PDS

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3219)

Boiling point/range°C: >200

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: >180

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: See PDS

pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: Please refer to Product Data Sheet (PDS) for grade specific typical properties.

[cont...]

SAFETY DATA SHEET

VARGEAR RANGE (ISO68 TO ISO460)

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: * Extremes of Temperature

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: * In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

[cont...]

SAFETY DATA SHEET

VARGEAR RANGE (ISO68 TO ISO460)

Page: 6

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Oil re-refining or other reuses of oil.

Waste code number: 13 02 05

Disposal of packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Product is not subject to authorisation under REACH.

15.2. Chemical Safety Assessment

Chemical safety assessment: * A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

[cont...]

SAFETY DATA SHEET

VARGEAR RANGE (ISO68 TO ISO460)

Page: 7

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



[final page]