











Medium Pressure  
**DIAMOND - High Abrasion**



VINCKE HH-24S

Two Wire Braid Hydraulic Hose meets or exceeds EN857 2SC

2SC PLUS SMOOTH DIAMOND Code	Nominal $\varnothing$		 Inside $\varnothing$	 Braid $\varnothing$	 Outside $\varnothing$	 Burst Pressure		 Max. Working Pressure		 Minimum Bend Radius	 Weight
	Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
24X04S	04	1/4"	6,4	11,1	13,2	1680	24360	420	6090	50	300
24X05S	05	5/16"	8	12,9	15	1520	22040	380	5510	55	340
24X06S	06	3/8"	9,5	15	17,1	1400	20300	350	5075	65	420
24X08S	08	1/2"	12,7	18,6	20,7	1240	17980	310	4495	90	540
24X10S	10	5/8"	16	21,7	23,8	1120	16240	280	4060	100	680
24X12S	12	3/4"	19	25,6	27,7	1080	15660	270	3915	120	800
24X16S	16	1"	25,4	33,3	35,5	740	10730	185	2683	150	1150



**Construction:** **Tube:** seamless oil resistant synthetic rubber

**Reinforcement:** 2 high tensile steel wire braid

**Smooth cover:** Super High abrasion and ozone, UV radiation, resistant synthetic rubber

**Fluid resistance:** Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

**Temperature range:** -40°C + 100°C Max (max 120°C intermittent)