

Male stud coupling  
Gerade-Einschraubverschraubung  
Union simple mâle

**P-GEV ..... R**

Stud thread: BSP thread (parallel),  
stud face form B

Einschraub-  
gewinde: Whitworth-Rohrgewinde (zylindrisch),  
Dichtkante Form B

Filetage mâle: Whitworth (cylindrique),  
arête d'étanchéité forme B

DIN-ISO 228 (R ..., DIN 259)

Series	bar	Tube OD		Type	Reference	kg per 100 pcs.	L <sub>5</sub>	L <sub>2</sub>	l	i	d	S <sub>1</sub>	S <sub>2</sub>
Reihe	PN	Rohr-AD		Typ	Best.-Nr.	kg per 100 St.							
Série	(psi)	Tube Ø ext.	G	Désignation	Réf.	kg par 100 p.							
LL	100 (1450)	4	G 1/8 A	<b>S-GEV 4 LLR</b>	<b>WAL038272</b>	1,8	13,5	19	9,5	8	14	14	10
		6	G 1/8 A	<b>S-GEV 6 LLR</b>	<b>WAL038274</b>	1,9	13,5	19,5	8	8	14	14	12
		8	G 1/8 A	<b>S-GEV 8 LLR</b>	<b>WAL038275</b>	2,3	14,5	20,5	9	8	14	14	14
L	400 (5801)	6	G 1/8 A	<b>P-GEV 6 LR</b>	<b>WAL373056</b>	2,5	15,5	23	8,5	14	14	14	14
		6	G 1/4 A	<b>P-GEV 6 L/R 1/4</b>	<b>WAL373057</b>	4,1	17	24,5	10	12	18	19	14
		6	G 3/8 A	<b>P-GEV 6 L/R 3/8</b>	<b>WAL602638</b>	6,0	18,5	26	11,5	12	22	22	14
		8	G 1/4 A	<b>P-GEV 8 LR</b>	<b>WAL373058</b>	4,5	17	25	10	12	18	19	17
		8	G 1/8 A	<b>P-GEV 8 L/R 1/8</b>	<b>WAL604871</b>	3,3	16,5	24	9,5	8	14	14	17
		8	G 3/8 A	<b>P-GEV 8 L/R 3/8</b>	<b>WAL373059</b>	6,0	18,5	26	11,5	12	22	22	17
		8	G 1/2 A	<b>P-GEV 8 L/R 1/2</b>	<b>WAL374844</b>	7,1	19	16,5	12	14	26	27	17
		10	G 1/4 A	<b>P-GEV 10 LR</b>	<b>WAL373060</b>	4,7	18	26	11	12	18	19	19
		10	G 3/8 A	<b>P-GEV 10 L/R 3/8</b>	<b>WAL373061</b>	6,0	19,5	27	12,5	12	22	22	19
		10	G 1/2 A	<b>P-GEV 10 L/R 1/2</b>	<b>WAL373062</b>	7,6	20	27,5	13	14	26	27	19
		12	G 1/4 A	<b>P-GEV 12 L/R 1/4</b>	<b>WAL373063</b>	6,3	19	27	12	12	18	19	22
		12	G 3/8 A	<b>P-GEV 12 LR</b>	<b>WAL373064</b>	9,5	19,5	27	12,5	12	22	22	22
		12	G 1/2 A	<b>P-GEV 12 L/R 1/2</b>	<b>WAL373065</b>	6,0	20	28	13	14	26	27	22
		15	G 3/8 A	<b>P-GEV 15 L/R 3/8</b>	<b>WAL373066</b>	11,5	20,5	28,5	13,5	12	22	24	27
		15	G 1/2 A	<b>P-GEV 15 LR</b>	<b>WAL373067</b>	16,5	21	29	14	14	26	27	27
		15	G 3/4 A	<b>P-GEV 15 L/R 3/4</b>	<b>WAL602629</b>	9,3	22	30	15	16	32	32	27
		18	G 1/2 A	<b>P-GEV 18 LR</b>	<b>WAL373068</b>	12,9	22	31	14,5	14	26	27	32
		18	G 3/4 A	<b>P-GEV 18 L/R 3/4</b>	<b>WAL374919</b>	18,0	22	31	14,5	16	32	32	32
	250 (3626)	22	G 3/4 A	<b>P-GEV 22 LR</b>	<b>WAL373069</b>	17,6	24	33	16,5	16	32	32	36
		22	G 1/2 A	<b>P-GEV 22 L/R 1/2</b>	<b>WAL374845</b>	17,5	24	33	16,5	14	26	32	36
		28	G 1 A	<b>P-GEV 28 LR</b>	<b>WAL373070</b>	24,7	25	34	17,5	18	39	41	41
		28	G 3/4 A	<b>P-GEV 28 L/R 3/4</b>	<b>WAL374846</b>	25,0	25	34	17,5	16	32	41	41
		35	G 1 1/4 A	<b>P-GEV 35 LR</b>	<b>WAL373071</b>	40,7	28	39	17,5	20	49	50	50
		42	G 1 1/2 A	<b>P-GEV 42 LR</b>	<b>WAL373072</b>	45,6	30	42	19	22	55	55	60
S	630 (9137)	6	G 1/4 A	<b>P-GEV 6 SR</b>	<b>WAL373073</b>	5,0	20	28	13	12	18	19	17
		8	G 1/4 A	<b>P-GEV 8 SR</b>	<b>WAL373074</b>	5,5	22	30	15	12	18	19	19
		8	G 3/8 A	<b>P-GEV 8 S/R 3/8</b>	<b>WAL374849</b>	8,0	22,5	30,5	15,5	12	22	22	19
		10	G 3/8 A	<b>P-GEV 10 SR</b>	<b>WAL373075</b>	8,2	22,5	31	15	12	22	22	22
		10	G 1/4 A	<b>P-GEV 10 S/R 1/4</b>	<b>WAL602938</b>	7,5	22	30,5	14,5	12	18	19	22
		10	G 1/2 A	<b>P-GEV 10 S/R 1/2</b>	<b>WAL374850</b>	13,0	25	33,5	17,5	14	26	27	22
		12	G 3/8 A	<b>P-GEV 12 SR</b>	<b>WAL373076</b>	9,5	24	33	17	12	22	22	24
		12	G 1/4 A	<b>P-GEV 12 S/R 1/4</b>	<b>WAL602939</b>	9,5	24	32,5	16,5	12	18	22	24
		12	G 1/2 A	<b>P-GEV 12 S/R 1/2</b>	<b>WAL373077</b>	13,5	25	34	17,5	14	26	27	24
		14	G 1/2 A	<b>P-GEV 14 SR</b>	<b>WAL373078</b>	14,8	27	37	19	14	26	27	27
		16	G 1/2 A	<b>P-GEV 16 SR</b>	<b>WAL373079</b>	15,4	27	37	18,5	14	26	27	30
		16	G 3/8 A	<b>P-GEV 16 S/R 3/8</b>	<b>WAL374852</b>	16,0	26,5	36,5	18	12	22	27	30
	400 (5801)	20	G 3/4 A	<b>P-GEV 20 SR</b>	<b>WAL373080</b>	25,3	31	42	20,5	16	32	32	36
		20	G 1/2 A	<b>P-GEV 20 S/R 1/2</b>	<b>WAL602651</b>	24,5	31	40	18,5	14	26	32	36
		25	G 1 A	<b>P-GEV 25 SR</b>	<b>WAL373081</b>	46,5	35	47	23	18	39	41	46
		25	G 3/4 A	<b>P-GEV 25 S/R 3/4</b>	<b>WAL374854</b>	45,5	35	47	23	16	32	41	46
	250 (3626)	30	G 1 1/4 A	<b>P-GEV 30 SR</b>	<b>WAL373082</b>	64,4	37	50	23,5	20	49	50	50
		38	G 1 1/2 A	<b>P-GEV 38 SR</b>	<b>WAL373083</b>	88,9	42	57	26	22	55	55	60
		38	G 1 1/4 A	<b>P-GEV 38 S/R 1 1/4</b>	<b>WAL603977</b>	89,6	42	57	26	20	49	55	60

L<sub>2</sub> = approximate length with nut tightened  
L<sub>2</sub> = Ungefährmaß bei angezogener Überwurfmutter  
L<sub>2</sub> = longueur approximative, l'écrou étant bloqué

