



Reservoir Accessories

Suction Strainer - SS

Specification:

- Reusable Stainless Steel 100 MESH/149 Micron Standard
- Nylon Nut
- Steel Cap/Support Tube
- Continuous Epoxy Bond
- Max. Working Temperature 80°C
- Suitable for hydraulic/mineral oil
- Consult factory - for water application
- Flexible magnetic wrap available



MODEL NO	FLOW LPM	THREAD IN. BSPP A	OVERALL LENGTH B	DIA NUT CAP C	NUT A/F	SCREEN AREA (SQ. CMS)	WT KGS	MAGNET WRAP
SS020-08	20	1 / 2	79	68	25	400	0 . 2 0	1
SS030-12	30	3 / 4	91	68	36	438	0 . 2 0	2
SS040-16	40	1	137	68	41	710	0 . 30	2
SS080-20	80	1 - 1 / 4	175	85	50	1045	0 . 4 5	2
SS120-24	120	1 - 1 / 2	206	85	59	1451	0 . 5 5	2
SS200-24	200	1 - 1 / 2	254	102	70	2193	0 . 6 5	2
SS200-32	200	2	254	102	70	2193	0 . 8 0	2
SS300-40	300	2 - 1 / 2	259	131	85	2580	1 . 0 5	3
SS400-48	400	3	300	131	96	3225	1 . 3 6	3