MORCLEAN LD 100

Page: 1

Compilation date: 29/11/2013

Revision date: 24-08-2015

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: MORCLEAN LD 100

Product code: CLA100

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Traffic film remover - cleaner

1.3. Details of the supplier of the safety data sheet

Company name: Harrier Fluid Power T/A Flowfit

Parys Road Ludlow Business Park Ludlow SY8 1XY United Kingdom

Tel: +44 (0)1584 876 033

Fax: +44 (0)1584 876 044 **Email:** sales@flowfitonline.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1584 876 033

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P260: Do not breathe mist.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.



MORCLEAN LD 100 TFR

Traffic Film Remover and Multipurpose Degreaser

Morclean LD 100 TFR is a multipurpose cleaner/degreaser formulated using high foaming surfactants, cleaning agents and alkalis for the removal of general dirt, traffic film and grease from vehicles and machinery.

Morclean LD 100 TFR has been developed for vehicle bodywork and machinery cleaning. Care should be taken when used at strong concentrations on polished aluminium.

Morclean LD 100 TFR can be diluted up to 100:1 depending on amount of road traffic film to be removed and hardness of local water. Application can be via pressure wash or brush and rinsed with clean water.

Applications			Features & Bei	nefits
 Removal of dirt, grease, traffic film and grime Bodywork Tautliner - curtain sided trailers Chassis Vans, Buses, Trucks Painted surfaces Floors and walls 			 Excellent performance characteristics High dilution ratio 100:1 Coloured product to aid selection and use Contains high foam surfactants and metasilicates Suitable for use with all types of vehicle cleaning systems High performance for arduous applications 	
Directions for use				
Brush Application	Brush Application 1%-1.5% High Pressure Washer 1% – 2%			
Adjust dilution depending	Adjust dilution depending on water hardness and pressure washer type			
When using pressure washer allow 5 minutes for activation before rinsing with clean water			lean water	
Shelf life 3 years from date of manufacture				
In use at 100:1 pH 10.0	In use at 100:1 pH 10.0 to 11.0			
Store sealed in a cool dry place between 5°C and 30°C				
For guidance on handling and disposal please refer to the Material Safety Data Sheet				
Morclean LD 100 TFR				
Characteristics	Typical Data	Cha	racteristics	Typical Data
Appearance	Amber liquid.	Spec	ific Gravity (@20°C)	1.06
Odour	Characteristic	PH (@ 1% concentration)	10.0 - 11.0
Solubility	Soluble in Water	PH (as supplied)	13.0 - 14.0
Flammability	Non Flammable			

rier Fluid Power Ltd T/A Flowfit, Parys Road, Ludlow Business Park, Ludlow, Shropshire SY. Telephone: +44 (0)1584 876 033 Fax: +44 (0)1584 876 044

Email: sales@flowfitonline.com

MORCLEAN LD 100

Page: 2

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

DISODIUM METASILICATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
229-912-9	6834-92-0	-	Skin Corr. 1B: H314; STOT SE 3: H335	1-10%
TETRASODIUM ETHYLENE DIAMINE TETRAACETATE				
200-573-9	64-02-8	-	Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%
SODIUM XYLENE SULPHONATE				
215-090-9	1300-72-7	-	Eye Irrit. 2: H319	1-10%
TRISODIUM NITRILOTRIACETATE				
225-768-6	5064-31-3	-	Carc. 2: H351; Acute Tox. 4: H302; Eye Irrit. 2: H319	<1%

Contains: *

Section 4: First aid measures

4.1. Description of first aid measures

 Skin contact:
 Remove all contaminated clothes and footwear immediately unless stuck to skin.

 Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

- **Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
 - Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
 - Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

MORCLEAN LD 100

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

MORCLEAN LD 100

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Empty containers retain product residue and can be hazardous.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC35: Washing and cleaning products (including solvent based products).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. The floor of the storage room must be	
	impermeable to prevent the escape of liquids. Ensure all engineering measures	
	mentioned in section 7 of SDS are in place.	
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.	
Hand protection:	Impermeable gloves.	
Eye protection:	Tightly fitting safety goggles. Ensure eye bath is to hand.	
Skin protection:	Impermeable protective clothing.	
Environmental:	Prevent from entering in public sewers or the immediate environment. The floor of the	
	storage room must be impermeable to prevent the escape of liquids. Ensure all	
	engineering measures mentioned in section 7 of SDS are in place.	

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid
Colour:	Yellow
Odour:	Barely perceptible odour
Evaporation rate:	Not applicable.
Oxidising:	No data available.
Solubility in water:	Soluble
Viscosity:	Non-viscous

MORCLEAN LD 100

[cont...]

Boiling point/range°C:	>35	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	>93	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	No data available.	pH:	>11.5
VOC g/I:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Extremes of Temperature

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DISODIUM METASILICATE

ORL	MUS	LD50	770	mg/kg
ORL	RAT	LD50	1153	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Page: 5

MORCLEAN LD 100

Symptoms / routes of exposure Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate. Eye contact: Corneal burns may occur. May cause permanent damage. Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose. Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing. Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal		
	company.		
Recovery operations:	Non Recoverable		
Waste code number:	11 01 11		
Disposal of packaging:	Empty containers should be taken to an approved waste handling site for recycling or		
	disposal		
NB:	The user's attention is drawn to the possible existence of regional or national		
	regulations regarding disposal.		

Section 14: Transport information

14.1. UN number

MORCLEAN LD 100

Page: 7

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Product is not subject to authorisation under REACh.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H314: Causes severe skin burns and eye damage.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H335: May cause respiratory irritation.
	H351: Suspected of causing cancer < state route of exposure if it is conclusively proven
	that no other routes of exposure cause the hazard>.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.