

ETJ-SERIES

ETJ-SERIES TOE JACKS

▶ Features

- ◆ Complies with ANSI/ASME B30.1, CE/GS standards.
- ◆ Designed for lifting loads with very low minimum clearance (foot) or high clearance (head).
- ◆ Can be used in confined spaces.
- ◆ Safety valve for overload protection.
- ◆ Features spring assisted return and over travel protection on 5 and 10 ton models.
- ◆ Electrically Forged base and cylinders to assure strength.



ETJ-105, ETJ-102

Model	Capacity(ton)		Min.Height(in)		Max.Height(in)		Toe Size(in)	Base size (in)	Weight (lbs)
	Toe	Head	Toe	Head	Toe	Head			
ETJ-102	2	3	0.63	9.37	5.06	13.74	1.97 × 1.97	5.00 × 7.01	17.6
ETJ-105	5	6	0.87	11.75	5.57	16.12	2.24 × 2.99	10.63 × 7.24	52.8
ETJ-110	10	14	1.12	13.13	6.81	18.13	2.36 × 4.02	11.26 × 9.53	83.6

▶ Features

- ◆ Complies with ANSI/ASME PALD standards and CE/GS.
- ◆ Compact and stable construction.
- ◆ Housing revolves 360 degrees.
- ◆ Lowering speed can be accurately adjusted.
- ◆ Protected against Overloading.
- ◆ Pump lever is removable.



ETJ-210, ETJ-205

Model	Capacity	Min.Height(in)		Max.Height(in)		Max Lever Force(kgf)	Weight (lbs)
	Ton	Toe	Head	Toe	Head		
ETJ-205	5	0.98	14.49	9.06	22.52	83.78	55.0
ETJ-210	10	1.18	16.54	10.24	25.59	88.19	55.0
ETJ-225	25	2.28	19.88	10.71	28.35	88.19	224.4