

High Peaks Pressure



Four High Tensile Spiral Hose meets or exceeds EN 856 4SH ISO 1307

VINCKE HH-04

EN 856 4SH										
Code	Nominal ø	Inside ø	Braid ø	Outside ø	Max. Working Pressure	Burst Pressure	Minimum Bend Radius	Weight		
Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
12	3/4"	19	28,2	32	420	6090	1680	24360	280	1465
16	1"	25,4	35,1	38,4	380	5510	1520	22040	340	2035
20	1 1/4"	31,8	41,9	45,2	350	5075	1400	20300	460	2385
24	1 1/2"	38,1	48,8	53	290	4205	1160	16820	560	3185
32	2"	50,8	63,2	67,6	250	3625	1000	14500	700	4365

Construction:

Tube: seamless oil resistant synthetic rubber

Reinforcement: 4 high tensile steel spiral

Wrapped cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C discontinuous)

HOSE TESTED OVER >400.000 DYNAMIC IMPULSE CYCLES (100°C)

