



DESCRIPTION	CODE	ORDER PART NUMBER	DRAWING
Particles counter monitor	FMSC01S0	04.006.00187	

Moisture and temperature sensor	F MSS01S0	04.006.00188	
---------------------------------	-----------	--------------	---

**ACCESSORIES**

DESCRIPTION	CODE	ORDER PART NUMBER	DRAWING
<p><b>Universal power supply</b>                      Input range: 100...240VAC 50/60Hz                      Output voltage: 24VDC / max. 0,63A / 15W                      Temperature range in operation: 0...40°C                      Compatible with data cable FMSA04S0                      Supply line: Euro power cord 2-pole, 1.5m</p>	FMSA01S0	04.006.00190	

<p><b>Data cable for computer connection</b>                      Side 1: M12 8-pole, 90° angled, IP67                      Side 2: D-Sub connector 9-pole with separate DC                      Plug for power supply                      Length: 5m, shielded                      Temperature range -25°C...90°C                      Oil-resistant</p>	FMSA04S0	04.006.00191	
---	----------	--------------	---

<p><b>Adapter USB - RS232 serial</b>                      Side 1 (PC): USB A plug                      Side 2 (periphery): D-Sub connector 9-pole                      Length: 1.8m                      Incl. driver CD for Windows 98 / ME / 2000 / XP                      / Win 7 / Win 8</p>	FMSA05S0	04.006.00194	
---	----------	--------------	---

<p><b>Data cable with open ends</b>                      Side 1: M12 8-pole, 90° angled, IP67                      Side 2: open                      Length: 5m, shielded                      Temperature range -25°C...90°C                      Oil-resistant</p>	FMSA03S0	04.006.00192	
--	----------	--------------	---

<p><b>Sensor connector</b>                      M12 8-pole, straight, IP67                      Suitable for cable diameter 6...8 mm                      Temperature range -20°C ... 85°C                      Oil-resistant</p>	FMSA02S0	04.006.00193	
---	----------	--------------	---

<p><b>Sensor adapter block for pipe installation</b>                      Line connectors 3/4"                      Material: Aluminum                      Pressure range: up to 50bar                      Oil-resistant</p>	FMSA06S0	04.006.00375	
--	----------	--------------	---

<p><b>Cable for power supply connection</b>                      Side 1: M12 8-pole, 90° angled, IP67                      Side 2: DC Plug for power supply                      Length: 5m, shielded                      Temperature range -25°C...90°C                      Oil-resistant</p>	FMSA07S0	04.006.00533	
--	----------	--------------	---