

Medium / High Pressure



Two Wire Braid Hydraulic Hose meets or exceeds DIN EN 853 2SN, SAE 100R2 AT and ISO 1436

VINCKE HH-22

2SN											
Code	Nominal ø		Inside ø	Braid ø	Outside ø	Max. Working Pressure		Burst Pressure		Minimum Bend Radius	Weight
	Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
VNK	03	3/16"	4,8	11,1	13,3	415	6018	1660	24070	90	295
VNK	04	1/4"	6,4	12,8	15	400	5800	1600	23200	100	375
VNK	05	5/16"	8	14,3	16,5	350	5075	1400	20300	115	430
VNK	06	3/8"	9,5	16,7	18,9	330	4785	1320	19140	130	540
VNK	08	1/2"	12,7	19,8	22,2	275	3988	1100	15950	180	640
VNK	10	5/8"	16	22,9	25,2	250	3625	1000	14500	200	750
VNK	12	3/4"	19	26,9	29,2	215	3118	860	12470	240	925
VNK	16	1"	25,4	34,8	37,2	165	2393	660	9570	300	1290
VNK	20	1 1/4"	31,8	44,3	47,3	125	1813	500	7250	420	1890
VNK	24	1 1/2"	38,1	50,7	53,7	90	1305	360	5220	500	2100
VNK	32	2"	50,8	63,5	66,7	80	1160	320	4640	630	2760
VNK	40	2 1/2"	63,5	75,2	79,8	69	1001	276	4002	760	4443
VNK	48	3"	76,2	87,4	91,9	50	725	200	2900	900	5459

